


219.00 EUR
incl. 19% VAT, plus [shipping](#)



- Intel® H81 Chipset
- Supports Intel LGA 1150 Socket 4th Generation Core™ i3, i5, i7 & Pentium Processors
- 2 * Dual Channel SO-DIMM DDR3-1333/1600 up to 16GB
- 1*HDMI output
- Support CPU Smart FAN
- Supports 1 * Gigabit LAN
- Supports ACPI S3 Function
- Support Watch dog Technology
- Thin Mini ITX form factor

• CPU	• INTEL® LGA 1150 Socket 4th generation Core i7/i5/i3/Pentium Processor
• Chipset	• INTEL® H81 Chipset
• Memory	• 2 * SO-DIMM Sockets Dual Channel DDR3 1600/1333 SDRAM up to 16 GB
• Expansion Slots	• 1 *PCIe x 1 • 1 * half size Mini PCI-E socket
• Storage	• 1 * Serial ATA2 3Gb/s & 1 * Serial ATA3 6Gb/s connectors • 1 * full size mSATA socket (only mSATA)
• Audio	• Realtek ALC662 6-Channel HD Audio CODEC
• Ethernet LAN	• Intel i217LM Gigabit Ethernet LAN *1
• USB	• 6* USB 2.0/1.1 & 2 * USB3.0
• Special Features	• Support ACPI S3 • Support CPU Smart FAN • Support Watch Dog

• Rear Panel I/O	<ul style="list-style-type: none"> • 2 * USB 2.0/1.1 & 2 * USB 3.0 ports • 1 * HDMI • 1 * DVI-I port • 1 * 19V DC-in jack • 1 * RJ-45 port • 1 * MIC-in & 1 * Line-out jacks
• Internal I/O	<ul style="list-style-type: none"> • 2 * USB 2.0/1.1 headers • CPU /System Fan connectors; • 1 * PS/2 header • 1 * 24-bits Dual CH LVDS & 1 * Inverter connector • 1 * CIR header • 1 * AUDIO header • 1 * Speaker header • 1 * DMIC header • 1 * Front panel header • 1 * FPD Brightness connector • 1 * 2-pin ATX Power header • 1 * 2-pin open case header
• BIOS	• AMI 64Mb DIP Flash ROM
• Form Factor	• Thin Mini ITX Form Factor (170mm x 170mm)
• Functional	• ATM, POS, AIO, Panel PC, Digital Signage
• Certificate	• CE, FCC, RoHS
• Temperature	<ul style="list-style-type: none"> • Operating within 0-60 centigrade • Storage within -20-85 centigrade