



289.00 EUR
incl. 19% VAT, plus [shipping](#)

- INTEL® Bay Trail-M N2930 SoC Processor (QC, 1.83G)
INTEL® Bay Trail-I E3827 SoC Processor (DC, 1.75G)
- Support 1 * DDR3L 1333/1066MHz Single CH up to 4GB
- Support 1 * Serial ATAll (3Gb/s) Devices
- Integrated Realtek ALC662 HD Audio CODEC with 2-CH
- 1 * 24 bits Dual Channel LVDS header
- Support DVI-I Output
- Supports 2 * Realtek RT8111G Gigabit LAN
- Support CPU Smart FAN
- 148 x 102mm 3.5" SBC Form Factor

| | |
|-------------------------|---|
| CPU | INTEL® Bay Trail-M N2930 SoC Processor (QC, 1.83GHz) |
| Chipset | N/A |
| Memory | 1 * DDR3L 1333/1066MHz Single CH SO-DIMM up to 4GB |
| Expansion Slots | 2 * MINI PCI-E (one share with mSATA) socket |
| Storage | 1 * Serial ATAll 3Gb/s connector 1 * mSATA socket |
| Audio | Realtek ALC662 HD Audio CODEC with 2-Channel |
| Ethernet LAN | 2 * RTL8111G PCI-E Gigabit LAN |
| USB | Embedded 1 * USB 3.0 + 7 * USB 2.0/1.1 |
| LVDS | Onboard 1 * 24-bits Dual channel LVDS connector |
| Rear Panel I / O | 1 * USB 3.0 port 3 * USB 2.0/1.1 ports 2 * RJ-45 ports 1 * Line-out port 1 * DVI-I port 1 * one-pin 9~24V DC-IN Jack |
| Internal I / O | 2 * USB 2.0 header for 4 * USB 2.0 ports 1 * KB/MS header 1 * Audio header & 1 * HDMI-SPDIF header Chassis Fan Connectors 1 * GPIO header 4 * COM headers (COM1 support RS232/422/485) & 4 * COM ports 5V/12V Selectable headers 1 * chassis intrusion header & 1 * AT mode selectable header |
| BIOS | AMI 64MB SMT Flash ROM |
| Form Factor | 3.5" SBC form factor (148mmx102mm) |

| | |
|--------------------|---|
| Certificate | CE,FCC,RoHS,ERP |
| Functional | ATM, Automation, Medical Equipment, Security, General Application, Transportation, Digital Signage, Kiosk, POS machine, LCD TV PC, Embedded Fanless application |
| Temperature | Operating within 0~60 centigrade Storage within -20-85 centigrade |