

389.00 EUR  
incl. 19% VAT, plus [shipping](#)

- JBC320U93W-2930-B



- INTEL® Bay Trail-M N2930 SoC Processor 1.83GHz, Quad-Core, 7.5W
- Embedded Long-life Series, 5 Year Availability
- NUC Form Factor (101mm X 101mm) Design for Fanless Systems
- 9V~24V DC jack on back panel for external power supply
- Additional 2.5" HDD Bay & 2 x HDMI & 2 x LAN
- ECO-design for EuP/ErP
- 2x HDMI & 2x Intel LAN

|                                  |   |  |
|----------------------------------|---|--|
| <b>Model No</b>                  | <b>JBC320U93-2930-B  <br/>JBC320U93-2930-S</b>                                  | <b>JBC320U93W-2930-B  <br/>JBC320U93W-2930-S</b>   |
| <b>Part No</b>                   | <b>HBJC320U93-2930-B  <br/>HBJC320U93-2930-S</b>                                | <b>HBJC320U93W-2930-B  <br/>HBJC320U93W-2930-S</b> |
| <b>Motherboard Specification</b> |   |  |
| <b>CPU</b>                       | Fanless INTEL® Bay Trail-M Celeron N2930 SoC Processor 1.83GHz, Quad-Core, 7.5W |  |
| <b>Memory</b>                    | 1 * 204-pin DDR3L-1333 SO-DIMM Single Channel up to 8 GB (1.35V required)       |  |

|                                  |   |                                       |
|----------------------------------|---|---------------------------------------|
| <b>VGA</b>                       | Intel® HD Graphics  |                                       |
| <b>LAN</b>                       | 2 x Intel® 82583V Gigabit Ethernet  |                                       |
| <b>Audio</b>                     | Realtek ALC887 Audio CODEC with SPDIF out   |                                       |
| <b>Storage</b>                   | 1 x full size mSATA Slot<br>1 x SATA2 3Gb/s for 2.5" HDD  |                                       |
| <b>Wireless / Mini-PCIE Slot</b> | 1 x half size Mini-PCI Express Slot   | Wireless 802.11 b/g/n + Bluetooth 4.0 |
| <b>Board Form Factor</b>         | NUC Form Factor (101mm X 101mm)   |                                       |
| <b>Chassis Specification</b>     |   |                                       |
| <b>Product size</b>              | 116 * 110 * 65 mm   |                                       |
| <b>Material</b>                  | Lightweight aluminum alloy with extruded aluminum IO panel  |                                       |
| <b>Color</b>                     | Black and Sliver  |                                       |
| <b>HDD</b>                       | 1 x Internal 2.5" HDD Bay   |                                       |
| <b>Front I/O Port</b>            | 1 * Power Button<br>1 * Power LED<br>1 * RS232/422/485 COM port<br>1 * USB 3.0<br>1 * USB 2.0   |                                       |
| <b>Rear I/O Port</b>             | 2 * USB 2.0 ports<br>2 * HDMI<br>2 * RJ-45 port<br>1 * Audio line out with SPDIF out<br>1 * 9V ~ 24V DC-in jack<br>2 * SMA Connector for WiFi Antenna<br>1 * Kensington Lock Hole                             |                                       |
| <b>Power</b>                     | Adapter : AC_90~240V / DC_12V_3A/36W  |                                       |
| <b>Environment</b>               | Operating Temperature : 0°C ~ 40°C with air flow<br>Storage Temperature : -20°C ~ 80°C  |                                       |
| <b>Standard Accessory</b>        | √ 36W AC Adapter x1<br>√ Power Cord x1<br>√ Screw pack x1<br>√ DVD Disk x1<br>√ Manual x1<br>√ WALL + VESA + DIN rail mounting kit (Black)<br>√ Din Rail Clip<br>√ WIFI antenna (with HBJC320U93W-2930 model) |                                       |
| <b>Functional</b>                | Digital Signage, Set Top Box, Thin Client, Car Entertainment, Smart Mini PC, POS/POI, KIOSK, HTPC   |                                       |
| <b>Certificate</b>               | CE,FCC,ErP For Barebone<br>CE,FCC,TUV,UL,CCC,CB,ErP For Power Adapter   |                                       |