



429.00 EUR
incl. 19% VAT, plus [shipping](#)

- J1900 !



- Intel® Bay Trail-D J1900 Processor
- Support DDR3L memory up to 8G (not included!)
- 1 * USB3.0 , 5 * USB2.0 , 4 * RS232 , 2 * RS232/422/485 , 1 * 3W Speaker , 1 * GPIO
- Form Factor : 185 x 142 x 48mm
- 9~24V DC-in Power

| | |
|-------------------|-------------------------------------------------------------------------------------------------|
| Dimensions | – 185 * 48 * 142 mm |
| Construction | – Aluminum housing |
| Product model | – HBJC376C55-1900 |
| MB model | – JNC55-E1900 |
| CPU | – INTEL® Bay Trail-D J1900 SoC Processor (2.0GHz) |
| BIOS | – AMI UEFI |
| Memory | – Support DDR3L Memory (Max 8G) |
| Storage Space | – 1 * 2.5" SATA Device (Max Height 9.5 mm) – 1 * m-SATA SSD Device (Mini PCI-E) |
| Display Interface | – 1 * HDMI (Max. resolution: 1920 * 1200@60Hz) – 1 * VGA (Max. resolution: 1920 * 1200@60Hz) |
| Network | – 2 * RJ45 (Giga Lan) – WiFi (option) |
| Audio | – 1 * Line out – 1 * Mic in |
| Front I/O Port | – 5 * USB 2.0 – 1 * USB 3.0 – 1 * Speaker con (R+/R-/L+/L-) |
| Rear I/O Port | – 6 * COM(COM5/COM6 Support RS232/422/485) – 1 * GPIO |
| Expansion Slot | – 1 * Mini PCI-E (Full-size) |

| | |
|------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power Source | <ul style="list-style-type: none">- DC 9■24V Jack input- Adapter : AC_90~240V / DC_12V_5A / 60W |
| Certification | <ul style="list-style-type: none">- EMC : CE , FCC- Safety : RoHS , ErP |
| Environment | <ul style="list-style-type: none">- Operating Temperature : -10 ~ 60°C- Storage Temperature : -20 ~ 70°C |
| Mounting Bracket | <ul style="list-style-type: none">- Wall mounting Kits |
| Packing | <ul style="list-style-type: none">- Net Weight■1.4KG- Gross Weight■2.7KG- Color Box Dimension■250(W) x 118 (D) x 295 (H) mm |