



598.00 EUR incl. 19% VAT, plus shipping



- 7" 320 nits high brightness TFT LCD with LED backlight
- 10-points Multi Capacitive Touch
- Streamlined enclosure for highly efficient heat dissipation
- · Enclosed in robust aluminum casing
- Edge-to-edge narrow bezel design and Fanless cooling system
- Design for easy Wall mount, Panel Mount, VESA Mount installation
- · A true Flat, easy-to-clean front surface with edge-to-edge design
- Front bezel meets IP65-rated protection

Jetway HPC070SC-FP2807A Flat-PanelFanless Panel PC provides outstanding outlook with industrial-grade quality for comprehensive industrial markets, such as retails, wholesales, hospitality, hospital or meeting room registration, logistics, self-service kiosk, residential automation and digital signage.

Jetway HPC070SC-FP2807A Flat-PanelFanless Panel PC is designed with 10-points Multi capacitive type touch screen. High brightness TFT LCD panel with LED backlight are equipped with this model. Streamlined enclosure with narrow bezel design.

Jetway HPC070SC-FP2807A Flat-Panel Fanless Panel PC are designed with a true flat, easy-to-clean front surface with edge-to-edge design. It is designed mounting clips for easy Wall mount, Panel Mount, VESA Mount installation.

Front bezel meets IP65-rated & NEMA 4 protection. Welcome to use Jetway Flat-Panel Panel PC.

Display	
Front Bezel	- IP65, NEMA 4 rugged protection, Full planar metal border



## Jetway HPC070SC-FP2807A Panel-PC (7" 1024x600 PCAP Touchscreen, Intel N2807, 2GB RAM) [IP65/NEMA4 Front]

[http://www.cartft.com/catalog/il/2352]

Display Type  Brightness (cd/m²)	- 7" With LED Backlight
Display Color	_ 16.7M
Resolution	- 1024 x 600 @ 60Hz
Viewing Angle (H/V)	- 150°/145°
Pixel Pitch	- 0.15 x 0.15 mm
Aspect Ratio	<b>–</b> 16:9
Contrast Ratio	- 500:1
Response Time	- 30 ms
Touch Screen	
Туре	- projected capacitive type
Active Range	- 152.40 x 91.44mm ±0.2mm
Transparency	<b>- ■</b> 85%
Surface Hardness	- ■6H (JIS-5400)
Glass haze value	<b>-■</b> 3%
CASE	
Panel Material	– Aluminum
Case Material	– Iron
Color	- Silver + white
Coating Requirement	- Spray Paint
Main System	
СРИ	- Intel® Bay Trail-M N2807 1.58GHz/DC
RAM	- 2G 1333MHz DDR3L SAMSUNG DRAM
BIOS	- 64MB SPI Flash ROM
Storage	- 1 * mSATA connector (Full size)
Watchdog Timer	- 256 levels, 0~255 sec.
OS Support	- Windows 7 / 8.1 / 10 / Linux (Option)
I/O Connector	
	- 1 * USB3.0
	- 1 * USB2.0
	- 1 * RS232/422/485
I/O Ports and Switches	- 1 * HDMI - 1 * LAN (Gigabit LAN)
	- 1 * Euro terminal block by 12V DC input
	– 1 * Power button
Expansion Interface	
Expansion	- 1 * PCI-E mini card for WIFI or 3G/4G
Power	
	Supports 12V DC Power in with over current protection fuse
Power Input	- Provides 100~240V AC-DC 12V, 60W power adapter
Power Consumption	– 13W
Dimension	
Case Dimensions	- 197.0*136.0*50.7mm
Certifications	
Certifications	- CE, FCC, IP65(Front)
Environment	



## Jetway HPC070SC-FP2807A Panel-PC (7" 1024x600 PCAP Touchscreen, Intel N2807, 2GB RAM) [IP65/NEMA4 Front]

[http://www.cartft.com/catalog/il/2352]

Temperature	Operating Temperature: -10 ~ 60° C (with W.T. DRAM/HDD in airflow condition)     Storage Temperature: -20 ~ 85° C	
Shock	<ul><li>Operating: 15G■11ms duration</li></ul>	
Vibration	- Operating: 5~500Hz/1 Grms	
Warranty		
Warranty	2 Years Limited Warranty(Panel and Touch is only Warranty 1 Year)	