



**CARTFT.COM**  
Shop for mobile  
PC- and GPS-Solutions

## Akasa Kepler R - 2U Rackmount Enclosure (for Intel Core Micro-ATX, Fanless) [A-ATX12-M1B]

[<http://www.cartft.com/catalog/il/3902>]

0.00 EUR

incl. 19% VAT, plus shipping



- **Micro-ATX Case !**
- **FANLESS !**
- **Redundantes Netzteil !**
- **A-ATX11-M1B !**

2U rack-mountable fanless case for Micro-ATX motherboards with 120W redundant, hot-swappable fanless ATX PSU. Supports processors up to 35W TDP with Intel® LGA1851/LGA1700 sockets. Features 4 front 2.5" SATA SSD/HDD hot-swap drive bays and 4 rear low-profile PCIe slots. Engineered for critical industrial server, control or telecommunication systems.

### Features :

- Compatible with Micro-ATX and Mini-ITX motherboards with processors up to 35W TDP (LGA1851/LGA1700)
- Fanless cooling and power supply design
- Four-bay 2.5" SATA SSD/HDD mobile rack with secure lock and tool-free installation
- Features four low-profile PCIe expansion slots
- Fits standard 19 inch server racks
- 120W redundant, hot-swappable fanless AC-to-DC power supply with active load sharing

### Material

Black sandblasted steel (SGCC) with aluminium heatsink

### Motherboard Type

Micro-ATX, Mini-ITX

### Socket Support

Intel® LGA1851, LGA1700

### Maximum TDP Support

35W

### Dimensions

481.8 x 307.5 x 87mm (W x D x H)

### Drive Bays

4 x 2.5" SATA SSD/HDD bays with door lock (maximum drive height of 9.5mm)

|                         |                                                                                                                                              |
|-------------------------|----------------------------------------------------------------------------------------------------------------------------------------------|
| Front I/O Interfaces    | 2.5" SATA SSD/HDD bays x4, USB 3.2 Gen 1 Type-A ports x2, power LED opening, HDD LED opening, power button                                   |
| Rear I/O Interfaces     | Low-profile PCIe slot x4, motherboard rear I/O opening, power AC inlet and switch                                                            |
| Power Supply Unit (PSU) | Redundant AC-to-DC power supply with multi-rail output<br>(redundant power output rated at 120W AC/DC (90-264 VAC))<br>Power Efficiency: 89% |
| Product Code            | A-ATX12-M1B                                                                                                                                  |