



139.95 EUR  
incl. 19% VAT, plus [shipping](#)

- VGA/HDMI Dual !
- 9-24VDC !
- 2x MiniPCle !
- 2x COM !

**Support:** [Specifications](#) | [Manual \[EN\]](#)

Limited offer. As long as stock lasts !

Excellent as a router. 2x Intel WG82574L Gigabit LAN connections, high NAT performance thanks to Intel 1.86Ghz Dual-Core Atom CPU, 3G / 4G / LTE / 5G modem or WLAN upgradeable via 2x mini-PCle slot. 2x COM port. Fanless, small, energy efficient, strong!

Scope of supply : DFI EC800-CD2041 (2GB RAM/16GB SSD), 12V 60W AC/DC power adapter with power cord, 2x metal mounting adapter

CPU	Intel® Atom™ D2550, 1.86GHz, 2x 512K L2, 10W TDP, dual-core
Chipset	Intel® NM10 Express Chipset
RAM	2GB DDR3 onboard
Graphics	Intel® GMA 3650 <ul style="list-style-type: none"> <li>• 1 VGA port supports display resolution up to 1920x1200</li> <li>• 1 micro HDMI port supports display resolution up to 1920x1080</li> <li>• Smooth Video Playback - Supports hardware decoders (H.264, VC-1, MPEG-4) with Full HD 1080p video playback capability</li> </ul>
Storage	<ul style="list-style-type: none"> <li>• 1 CFAST socket</li> <li>• 1 mSATA module via a Mini PCIe slot (16GB Module included)</li> </ul>
Ethernet	2x Intel® WG82574L Gigabit Ethernet controllers (DUAL LAN)
Audio	<ul style="list-style-type: none"> <li>• Realtek® ALC886 7.1-channel High Definition Audio</li> <li>• 1 line-out and 1 mic-in</li> </ul>
COM	<ul style="list-style-type: none"> <li>• 2 DB-9 ports (RS232/422/485)</li> <li>• Supports RS485 auto direction control</li> </ul>

---

Expansion	<ul style="list-style-type: none"><li>• 3 Mini PCIe slots - 2 slots for communication : One slot supports PCIe x1, USB, and LPC signals for Wi-Fi module or LPC module : One slot supports PCIe x1, USB, and 3G signals for 3G or GPRS module - 1 slot for storage : Supports mSATA module</li><li>• 1 SIM card socket</li><li>• 1 CFast</li><li>• 1 DB-9 RS232/422/485 COM</li><li>• 1 mic-in• 2 LAN• 4 USB 2.0 (Type A)</li><li>• 1 CFast socket</li></ul>
Front I/O	<ul style="list-style-type: none"><li>• 1 status LED</li><li>• 1 hdd LED</li><li>• 1 reset button</li><li>• 1 power button with LED</li></ul>
Power	9~24V DC power input voltage
Environment	<ul style="list-style-type: none"><li>• Temperature - Operating: 0oC ~ 60oC - Storage: -40oC ~ 80oC</li><li>• Humidity - Operating: 10% to 85% non-condensing - Storage: 10% to 90% non-condensing</li></ul>
Construction	Aluminium
Mounting	Wall/VESA/DIN Rail mount
Dimensions	161mm x 32mm x 108.2mm (W x H x D)
Weight	700g
OS Support	<ul style="list-style-type: none"><li>• Windows XP, WES 2009, POSReady 2009</li><li>• Windows 7 (32-bit), WES 7 (32-bit)</li><li>• Linux</li></ul>
Other features	Watchdog Timer function
Certification	<ul style="list-style-type: none"><li>• CE</li><li>• FCC Class A</li><li>• RoHS</li><li>• UL</li><li>• CCC</li><li>• KC</li></ul>