



199.95 EUR
 incl. 19% VAT, plus [shipping](#)

- Intel Celeron BayTrail !
- Dual Gigabit LAN !
- Win7, Win 8 !



- Built-in Intel® Celeron™ J1900 (2.0 GHz) quad-core processor
- GIGABYTE Ultra Durable™ 4 Plus Technology
- All Solid Capacitors with Humidity Protection New Glass Fabric PCB design
- Dual LAN with high ESD Protection
- GIGABYTE UEFI DualBIOS™
- DVI-D, D-SUB ports on rear panel
- Ample USB 3.0 ports with GIGABYTE 3x USB power
- GIGABYTE On/Off Charge™ for USB devices
- Mini PCI-E expansion slot supports wireless networking cards
- PCI expansion slot supports legacy interface cards

1. Built in with an Intel® Celeron® Quad-Core J1900 SoC (2.0 GHz)
 * Do not disassemble the onboard SoC and the heatsink by yourself to avoid damage to these components.
2. 2 MB Cache

CPU

	<ol style="list-style-type: none">1. 2 x DDR3/-L SO-DIMM sockets supporting up to 8 GB of system memory * If only one DDR3/-L memory module is to be installed, be sure to install it in the SODIMM_1 socket.
Memory	<ol style="list-style-type: none">2. Dual channel memory architecture3. Support for DDR3/-L 1333 MHz memory modules4. Support for non-ECC memory modules
	Integrated in the SoC:
Onboard Graphics	<ol style="list-style-type: none">1. 1 x D-Sub port, supporting a maximum resolution of 2560x16002. 1 x DVI-D port, supporting a maximum resolution of 1920x1080 * The DVI-D port does not support D-Sub connection by adapter.
	<ol style="list-style-type: none">1. Realtek® ALC887 codec2. High Definition Audio
Audio	<ol style="list-style-type: none">3. 2/4/5.1/7.1-channel * To configure 7.1-channel audio, you have to use an HD front panel audio module and enable the multi-channel audio feature through the audio driver.4. Support for S/PDIF Out
LAN	<ol style="list-style-type: none">1. 2 x Realtek® GbE LAN chips (10/100/1000 Mbit)
	<ol style="list-style-type: none">1. 1 x PCI slot
Expansion Slots	<ol style="list-style-type: none">2. 1 x Mini PCI Express x1 slot (The Mini PCI Express slot conforms to PCI Express 2.0 standard.) (For Mini-PCIE card/no mSATA card)
	Integrated in the SoC:
Storage Interface	<ol style="list-style-type: none">1. 2 x SATA 3Gb/s connectors
	Integrated in the SoC:
USB	<ol style="list-style-type: none">1. 2 x USB 2.0/1.1 ports (available through the internal USB header)
	SoC + Renesas® uPD720210 USB 3.0 Hub:
	<ol style="list-style-type: none">1. 4 x USB 3.0/2.0 ports on the back panel

	<ol style="list-style-type: none">1. 1 x 24-pin ATX main power connector2. 1 x 4-pin ATX 12V power connector3. 2 x SATA 3Gb/s connectors4. 1 x CPU fan header5. 1 x system fan header6. 1 x front panel header
Internal I/O Connectors	<ol style="list-style-type: none">7. 1 x front panel audio header8. 1 x S/PDIF Out header9. 1 x USB 2.0/1.1 header10. 1 x parallel port header11. 1 x Clear CMOS jumper12. 1 x chassis intrusion header13. 1 x debug card header
Back Panel Connectors	<ol style="list-style-type: none">1. 1 x PS/2 keyboard port2. 1 x PS/2 mouse port3. 1 x D-Sub port4. 1 x DVI-D port5. 2 x serial ports6. 4 x USB 3.0/2.0 ports7. 2 x RJ-45 ports8. 3 x audio jacks (Line In, Line Out, Mic In)
I/O Controller	<ol style="list-style-type: none">1. iTE® I/O Controller Chip
H/W Monitoring	<ol style="list-style-type: none">1. System voltage detection2. CPU/System temperature detection3. CPU/System fan speed detection4. CPU/System fan speed control <p>* Whether the fan speed control function is supported will depend on the cooler you install.</p>

BIOS	<ol style="list-style-type: none">1. 2 x 64 Mbit flash2. Use of licensed AMI UEFI BIOS3. Support for DualBIOS™4. PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0
Unique Features	<ol style="list-style-type: none">1. Support for @BIOS2. Support for Xpress Install3. Support for APP Center * Available applications in APP Center may differ by motherboard model. Supported functions of each application may also differ depending on motherboard specifications.4. Support for ON/OFF Charge
Bundle Software	<ol style="list-style-type: none">1. Norton® Internet Security (OEM version)2. Intel® Smart Connect Technology
Operating System	<ol style="list-style-type: none">1. Support for Windows 8.1/8 32-bit/64-bit2. Support for Windows 7 64-bit * To support Windows 7 64-bit, please update the latest BIOS and drivers.
Form Factor	<ol style="list-style-type: none">1. Mini-ITX Form Factor; 17.0cm x 17.0cm
Remark	<ol style="list-style-type: none">1. Due to different Linux support condition provided by chipset vendors, please download Linux driver from chipset vendors' website or 3rd party website.2. Most hardware/software vendors may no longer offer drivers to support Win9X/ME/2000/XP SP1/SP2. If drivers are available from the vendors, we will update them on the GIGABYTE website.