



569.00 EUR

 incl. 19% VAT, plus [shipping](#)

- wlan !



- Intel® LGA1151 Socket Core I3,I5,I7 Pentium Processor
- Intel® Coffee Lake■S H310 Chip
- Support Dual Channel DDR4 2133MHz up to 32GB
- 1\* Intel®I219■VGiga LAN + 1\* Intel® i255V 2.5Gb LAN
- Support 1\* SATA III (6Gb/s) & M.2 (M key 2242)
- 1\* M.2 E key Support CNVi
- 4\* RS232 (COM1/2 Support 5V/12V TTL, 4\* USB3.0
- Support HDMI/VGA /EDP (Option)
- DC 12~24V Input

Model	– HBJC501C8HV-H310 – HBJC501C8HVI-H310 (Wifi)
CPU/Chipset	– Intel® LGA1151 Socket Core I3,I5,I7 Pentium Processor (TDP 35W) – Intel® Coffee Lake-S H310 Chip
BIOS	– AMI 128MB SMT Flash ROM
Memory	– 2* DDR4 2133MHz up to 32GB
Network	– 1* Intel® I219-V GbE – 1* Intel® I225-V 2.5GbE – 1* WIFI2.4/5G + BTv4.1 (M.2 E key)
Graphics	– 1* HDMI (Max. Resolution : 4096x2160@30Hz) – 1* VGA (Max. Resolution: 1920x1080@60Hz) – 1* eDP (Option, Max. Resolution: 4096x2304@60Hz) – Support Dual Displays or Triple Displays with eDP
Storage	– 1* 2.5" SATA 6Gb/s internal drive bay (only support 2.5" HDD with a hight ≤ 10mm) – 1* M.2 (M-key 2242)
Expansion slot	– 1* PCIe x4 slot – 1* WIFI2.4/5G + BTv4.1 (M.2 E key)
Rear Panel I/O	– 4* USB3.0 – 1* HDMI – 1* VGA – 1* eDP – 2* RJ45 – 4* RS232 – 1* Line-out +MIC – 1* DC Jack – 1* Power Button

---

Front Panel I/O	– NA
Internal Connector	– NA
Compliance	– CE, FCC, RoHS, ErP Ready (option)
Power Source	– MB: DC 12~24V input – Adapter: AC_90~240V/ DC_19V / 120W
Temperature	– Operating Temperature: -10 ~ 50° C – Storage Temperature: -20 ~ 60° C – Humidity: 10% ~ 90% RH @40°C (non-condensing)
Dimensions	– System: 264 (W) x 199.4 (D) x 58 (H) mm
OS Support	– Windows 10, Linux