



1389.00 EUR
 incl. 19% VAT, plus [shipping](#)

- Intel Tiger Lake !
- HBJC38AZ02 Series !

| | |
|----------------|--|
| Part No. | - HBJC38AZ02 SERIES |
| BIOS | - AMI Flash ROM |
| CPU/Chipset | - Intel® Taigerlake-UP3 Soc Processor (i5-1145G7/default) |
| Memory | 2* DDR4 3200MHz SO-DIMM up to 64GB |
| Graphics | Intel HD Graphics, shared memory 2 * DP (Max Resolution: 4096x2304@60Hz) 1 * HDMI 2.0 (Max Resolution: 4096x2160@60Hz) |
| Network | - 1 * Intel i219LM GbE - 1 * Intel i225V GbE |
| Storage | - 1 * M.2 M-key 2242/2280 (SATA/PCIe Gen4 x4 Interface support NVMe) - 1 * 2.5" SATA HDD (6Gb/s) |
| Expansion | - 1 * M.2-2230 E-Key (USB2.0/PClex1 for WiFi support CVNi) - 1 * M.2-3042/3052 B-Key (USB3.1/USB2.0/PCIe x1 for 4G&5G expansion) - 1 * SIM Card Adapter (Internal) |
| Rear Panel I/O | - 2 * USB 2.0 - 2 * USB 3.2 (Gen.2) - 1 * DP, 1 * HDMI - 2 * RJ45 (2.5Gbps/1.0 Gbps) - 1 * Line out, 1 * MIC combo - 2 * COM (TOP: co-lay GPÜIO, Bottom: SUpport RS 232) - 1 * DC Jack (Lock Type) - 3 * Antenna holes (Optional) |

| | |
|-----------------|---|
| Front Panel I/O | <ul style="list-style-type: none"> - 1 * Power Button + LED - 1 * HDD LED - COM (By Model) - Intel LAN (By Model) - GPIO (8-bits IN & 8-bits OUT / by Model) - USB3.0 (by Model) |
| Power Source | <ul style="list-style-type: none"> - Adapter / AC 100~240V input / DC19V-90W - MB : DC 12~24V input |
| Compliance | <ul style="list-style-type: none"> - CE, FCC, LVD, RoHS, |
| Temperature | <ul style="list-style-type: none"> - Operating Temperature: -20 ~ 50° C (Under the condition of using M.2 interface SSD) (The test environment is closed and windless) - Storage Temperature: -20 ~ 70° C - Humidity : 40% ~ 60% RH (non-condensing) |
| Dimensions | <ul style="list-style-type: none"> - 185 (W) x 175 (D) x 60 (H) mm |
| OS Support | <ul style="list-style-type: none"> - Windows 11, Linux |