



148.00 EUR

 incl. 19% VAT, plus [shipping](#)

- VIA C7 NanoBGA CPU
- 1.5 Ghz !
- DDR-II !
- 12W

This board is based on the latest VIA C7 architecture.

7F2WE-1G5-OC Specifications	
Processor	VIA C7 1.5 GHz processor
Chipset	VIA CN700 north bridge
	VIA VT8237R south bridge
System Memory	1 DDR2 400/533 DIMM
	Up to 1GB memory size
VGA	Integrated VIA UniChrome AGP graphics
Expansion Slots	1 PCI
Onboard IDE	4 Ultra DMA 133
Onboard Serial ATA	2 SATA connectors
Onboard Floppy	1 Floppy Port
Onboard USB	8 USB 2.0
Onboard LAN	VIA 6103 10/100
Onboard Audio	ALC655 6 channel AC'97 codec
Onboard TV Out	VIA VT1622A TV encoder
Onboard 1394	IEEE 1394

Back Panel I/O	<ul style="list-style-type: none"> 1 1394 1 RCA video 1 VGA port 2 USB 2.0 1 LAN port 2 IEEE 1394 ports 1 serial ports 1 PS2 mouse port 1 PS2 keyboard port 3 audio jacks: line-out, line-in, and mic-in
Onboard I/O Connectors	<ul style="list-style-type: none"> 3 USB 2.0 connectors for 6 USB ports 1 parallel port 1 VGA port 2 serial ports 1 PS2 keyboard connector 1 PS2 mouse connector 1 floppy port Line-in/out/MIC audio ports
BIOS	<ul style="list-style-type: none"> Award BIOS LPC 4Mbit Flash memory
System Monitoring & Management	<ul style="list-style-type: none"> CPU temperature Modem ring wake up RTC Alarm Keyboard power on System temperature System voltage Fan speed
Operating Humidity	<ul style="list-style-type: none"> 0% - 95% (relative humidity; non-condensing)
Form Factor	<ul style="list-style-type: none"> Mini-ITX (17cm x 17cm)
Includes	<ul style="list-style-type: none"> ATA 133 flat cable (40 wire, 80 conductor, 3 connectors) CD SATA Cable Floppy Cable