

DH150 15 inch touch Panel PC

DH150 is a 15 inch all-in-one computing system with Intel Core-i level performance and multi-touch functionality, protected by IP65 front chassis design. All of these are aiming to provide the most stable and reliable quality for different environmental or industrial applications.



Retail Terminal

- Retail POS Terminal
- Self service Terminal
- Hospitality Terminal



Display System

- Digital Signage Player
- Clinical Monitor
- Transportation Display



the best regional partners

Industrial Automation

- Automation Controller
- Embedded Device Dashboard
- Production Line Controller

www.mitac.com



DH150



CORE Haswell+Q87







Dual GLAN



rt Wireless

FC C E

Specifications

| LCD Display | Size/Resolution | 15" TFT LCD, 1024 x 768, 4:3 |
|------------------|--------------------|---|
| | Luminance | 250 cd/m2 |
| | Viewing Angle | 85° (L/R), 80° (U/L) |
| Touch Screen | Туре | P-CAP multi-touch, Flat Glass |
| Processor System | Form Factor | Thin Mini-iTX, 170 x 170mm |
| | CPU | Intel Haswell LGA1150 CPU Socket H3 (up to 65W) |
| | Chipset | Intel Lynx Point Q87 Chipset |
| | Memory | 2 x DDR3-1600 SO-DIMM, up to 16GB |
| | Storage | 1 x 2.5" drive bay |
| | Expansion | x 1 PCI Express x 4 slot |
| | | x 1 PCI Express Full-/Half-Mini Card slot |
| | | x 1 PCI Express Half-Mini Card slot |
| | Ι/Ο | 2 x RJ-45; 4 x USB 3.0, 1x Line-Out, 1x Mic-In |
| | | 1x HD-out, 1x DP-out, 2 x RS-232 |
| Power | Input | 12/19V DC-in connectivity |
| | Power consumption | 120W adaptor |
| | Power On | AT (on when power is ready) |
| Mechanical | Size (W x D x H) | 280 mm x 380 mm x 82 mm |
| | Weight | ~5 kg |
| | Protection | IP65 Compliant in front |
| | Fixture | VESA 75x75/100x100mm, panel Mount |
| Environmental | Operating Temp | 0~50°C |
| | Operating Humidity | 10% ~ 90% (relative, non-condensing) |
| | Certification | CE/FCC Class A |

Dimensions



